

RMC REFRESH ECO

Rubio® Monocoat Refresh Eco is a ready-to-use sprayable product that refreshes and restores all wooden surfaces that have been treated with oil. Depending on wear and tear, RMC Refresh Eco can be applied several times a year at certain areas. This may be necessary if the surface feels dry.

RMC Refresh Eco is not pigmented. To restore the colour, use RMC Oil Plus 2C in the colour with which the surface area was treated.



PRODUCT INFORMATION

› Technical characteristics

- Physical state: liquid
- Colour: white
- Odour: characteristic
- Density: 1 kg/L
- Solubility: completely soluble
- VOC content: 0 g/L

› Packaging

Ecospray 0,5L and 1L

› Storage

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Do not allow to freeze.

APPLICATION INFORMATION

› Instructions

STEP 1. Clean the surface to be treated with RMC Soap or RMC Surface Care. Let it dry.

STEP 2. Spray a little amount of RMC Refresh Eco on the surface to be treated.

STEP 3. Spread out the product in the direction of the fibres of the wood with the RMC Microfiber Pad or a microfiber cloth.


STEP 4. Let it dry for at least 1 hour before using the surface again.

› Consommation

1L = ± 100 m²

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

› Tools



› Related products



RMC Soap



RMC Surface Care

Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit www.rubiomonocoat.com

YOUR DISTRIBUTOR:

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 25/01/2018. Check the safety information before using the product.**



Rubio[®]
MONOCOAT

MUYLLE  FACON

Muylle Facon BVBA
Ambachtenstraat 58
8870 Izegem (BELGIË)

Tel. +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubiomonocoat.com